

India's highest biogas plant commissioned at Leh-Ladakh

Biogas, which is generated from organic digestion under anaerobic conditions by mixed population of microorganisms, is an alternative energy source, that is now being utilized both in rural and industrial areas. Biogas technology offers an attractive route to utilize certain categories of biomass for meeting partial energy needs. Unlike other forms of renewable energy, biogas does not have any geographical limitations and required technology for producing energy and it is neither complex nor monopolistic¹. Spearheading the effort to tap alternate sources of energy in remote areas, the Defence Institute of High Altitude Research (DIHAR), a constituent laboratory of the Defence Research and Development Organisation (DRDO), has commissioned India's highest biogas plant at Leh-Ladakh at an altitude of 3500 m amsl. It has been set up in collaboration with the Bhabha Atomic Research Centre (BARC), Mumbai for various R&D purposes. It is also the world's second highest biogas plant; the world's highest biogas plant has been established by Nepal at Langtang Valley at 3850 m amsl.

The basic design of the plant is based on a dual process employing partial aerobic digestion followed by anaerobic

digestion. It produces biogas and organic manure (soil conditioner) based on the process of biomethanation. The organically rich biodegradable portion of solid waste is mixed with recycled water to form a slurry. The slurry is then aerobically digested in a predigester, where organic matter is converted to organic acids. The predigestion is accentuated by the addition of hot water and intermittent aeration. Predigestion reactions are exothermic and the temperature rises to 40°C. Hot water obtained using solar energy is added to raise this temperature to 50°C. The predigested slurry is further digested under anaerobic conditions for about 15 days. The process of methanogenesis of the acidified slurry takes place in this digester. The plant is fed with cattle dung, horse and poultry manure generated at the DIHAR farm.

The capacity of the biogas plant is 0.5 t/day and will generate about 35–50 m³ of biogas per day during the processing of biodegradable waste. This can be either fed to a gas engine alternator set of 25 kVA capacity to generate electricity for a period of 4–5 h everyday or can be used for cooking/boiler purposes [1.5–2.1 m³ of biogas (depending on the methane content of 50–65%) is equiva-

lent to 1 litre of diesel in terms of heat output.] Not only is biogas a fuel for producing green energy, but it also reduces greenhouse gases and may qualify for green credits (<http://www.epa.gov/agstar/resources.html>). About 25–40 kg/day (on weight basis) high-quality organic manure will be available from the plant which is rich in nitrogen, phosphorus, potassium and iron and devoid of any heavy metals and weed seed. Therefore, the generated organic manure can be utilized in agricultural fields to improve soil fertility as well as productivity.

-
1. Balat, M. and Balat, H., *Energy Sources, Part A: Recovery, Utilization, Environ. Effects*, 2009. **31**(4), 1280–1293.
-

S. ACHARYA*
S. B. MUSTAFA
B. PRAKASH
S. B. SINGH

*Defence Institute of High Altitude Research,
Defence Research and Development Organisation,
c/o 56 APO,
Leh-Ladakh 901 205, India
e-mail: someniari@gmail.com

Role of Integrated Watershed Management Programme in controlling erosion and reclaiming wastelands in India

India has about 55.27 million hectares (m ha) of wasteland. These are not suitable for any purpose and are exposed to the vagaries of nature like weathering, gully erosion, etc. The Department of Land Resources of the Ministry of Rural Development has been implementing three area development programmes since 1995, viz. Integrated Watershed Development Programme, Drought Prone Areas Programme and Desert Development Programme on watershed basis. These programmes have been merged into a single programme called the Integrated Watershed Management Programme (IWMP) since 2006 and above

38.2 m ha of wasteland has been developed into cultivable land.

Watershed or a drainage basin is a unit draining run-off water to a common point. Watershed management is the process of guiding and organizing the use of land and other resources in a watershed to provide goods and services desired without adversely affecting the soil and water resources. So far as water resources in India are concerned, only 35% of rainfall is captured and the rest flows as run-off. Almost 60% of the captured precipitation is lost again in evaporative transpiration due to open storage. The need of the hour is to regenerate the

natural resources that have degraded through land mismanagement in the last 50 years or so. India today has about 18% of the world's population and 15% of livestock population to be supported from only 2% of the world's geographical area and 1.5% of forest pasture land and 4% of water resources.

A micro-watershed is the basic unit of development, whose average area is around 500 ha. With the objective of water and soil conservation different structures such as contour bunds, contour trenching, minor pit, gully plugging, loose boulder check dams, and check dams are implemented in the micro-watershed.